

June 19, 2006
Case No.: 18534.53 (8125/4)
Serial No.: 10/716,094
Filed: November 18, 2003
Page 2 of 13

CLAIM AMENDMENTS

A listing of an amended set of claims 1-18 and a withdrawn set of claims 19 and 20 is submitted herewith per 37 CFR §1.121. This listing of claims 1-20 will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A computer servicing cart comprising:
an outer cabinet;
a first battery servicing compartment disposed in the outer cabinet for selectively charging one or more batteries; [and]
a first computer storage compartment disposed in the outer cabinet and including a first electrical outlet for selectively charging one or more computers;
a first internal power supply for providing power to the at least the first battery servicing compartment; and
a power shedding circuit including
a current sensing device operable to be in electrical communication with an external electrical outlet, the current sensing device including means for providing a signal indicative of a current drawn from the external electrical outlet,
a first relay in electrical communication with the first internal power supply, the first relay including means for selectively connecting the first internal power supply to the first computer storage compartment, and
a logic circuit in electrical communication with the current sensing device and the first relay, the logic circuit including means for operating the first relay based on a comparison of the current being drawn from the external electrical outlet as indicated by the signal to a predefined limit.
2. (Original) The computer servicing cart of claim 1 where the first internal power supply is selectively connectable to the external electrical outlet.

June 19, 2006
Case No.: 18534.53 (8125/4)
Serial No.: 10/716,094
Filed: November 18, 2003
Page 3 of 13

3. (Currently Amended) The computer servicing cart of claim 1 wherein the first computer storage compartment further [comprises] includes:
 - at least one shelf;
 - at least one electrical outlet adjacent to each shelf; and
 - at least one compartment adapted to conceal at least one AC/DC adapter for use with a computer.
4. (Currently Amended) The computer servicing cart of claim [2] 3 wherein:
 - each shelf adjusts vertically;
 - each shelf is tilted downward toward a back end at a predetermined angle;
 - each shelf has a recessed portion near a front end adapted to facilitate insertion and removal of computers; and
 - each shelf has a retainer adapted to guide an adapter cord to the computer.
5. (Currently Amended) The computer servicing cart of claim 1 wherein the outer cabinet [further comprises] includes a plurality of wheels.
6. (Original) The computer servicing cart of claim 1 further comprising a cooling system.
7. (Currently Amended) The computer servicing cart of claim 1 wherein the first battery servicing compartment further [comprises] includes a storage system adapted for storing the one or more batteries.
8. (Original) The computer servicing cart of claim 7 wherein the first battery servicing compartment is adaptable to store and charge different battery types.

June 19, 2006
Case No.: 18534.53 (8125/4)
Serial No.: 10/716,094
Filed: November 18, 2003
Page 4 of 13

9. (Currently Amended) The computer servicing cart of claim 1 further comprising:
a second internal power supply;

a second computer storage compartment; [and]

wherein [a power shredding circuit,] the power shredding circuit [comprising:] further includes

[a current sending device adapted to measure current drawn from the external electrical outlet;]

[a first relay adapted for controlling power to the first computer storage compartment;]

a second relay [adapted for controlling power to the second computer storage compartment] in electrical communication with the first internal power supply, the second relay including means for selectively connecting the first internal power supply to the second computer storage compartment; and

[a logic circuitry adapted for]:

wherein the logic circuit includes:

means for closing the first and second relays, and activating the second power supply in a predetermined order when the first power supply is activated;

means for opening the relays and deactivating the second power supply in a predetermined order when the current sensing device indicates [a] the current being drawing from the external electrical outlet in excess of [a] the predefined limit;\

means for recording a relay or power supply and a current drawn by the relay or power supply that cause the current drawn that is over the predefined limit;

means for monitoring the current drawn from the external electrical outlet such that a deactivated power supply or an opened relay can be activated or closed respectively when the current drawn from the external outlet has fallen enough to allow reactivation or closing without causing current to be drawn that is in excess of the predefined limit; and

means for deactivating the second power supply and opening the first and second relays when the first power supply is deactivated.

June 19, 2006
Case No.: 18534.53 (8125/4)
Serial No.: 10/716,094
Filed: November 18, 2003
Page 5 of 13

10. (Currently Amended) A computer servicing cart comprising:
- a first battery servicing module for selectively charging one or more batteries;
 - a first computer storage module [containing] including at least one electrical outlet for selectively charging one or more computers; [and]
 - a first internal power supply for providing power to the at least the first battery servicing module; and
 - a power shedding circuit including
 - a current sensing device operable to be in electrical communication with an external electrical outlet, the current sensing device including means for providing a signal indicative of a current drawn from the external electrical outlet,
 - a first relay in electrical communication with the first internal power supply, the first relay including means for selectively connecting the first internal power supply to the first computer storage module, and
 - a logic circuit in electrical communication with the current sensing device and the first relay, the logic circuit including means for operating the first relay based on a comparison of the current being drawn from the external electrical outlet as indicated by the signal to a predefined limit.
11. (Currently Amended) The computer servicing cart of claim 10 where the first internal power supply is selectively connectable to [an] the external electrical outlet.
12. (Currently Amended) The computer servicing cart of claim 10 wherein the first computer storage module further [comprises] includes:
- at least one shelf;
 - at least one electrical outlet adjacent to each shelf; and
 - at least one [module] compartment adapted to conceal at least one AC/DC adapter for use with a computer.

June 19, 2006
Case No.: 18534.53 (8125/4)
Serial No.: 10/716,094
Filed: November 18, 2003
Page 6 of 13

13. (Original) The computer servicing cart of claim 12 wherein:
at least one shelf adjusts vertically;
at least one shelf is tilted downward toward a back end at a predetermined angle;
at least one shelf has a recessed portion near a front end adapted to facilitate insertion and removal of computers.
14. (Currently Amended) The computer servicing cart of claim 10 wherein the first battery servicing [compartment] module further [comprises] includes a storage system adapted to store the one or more batteries.
15. (Currently Amended) The computer servicing cart of claim 14 wherein the first battery servicing module is adaptable to store and charge different battery types [respectively].
16. (Currently Amended) The computer servicing cart of claim 10 further comprising a wheeled transport module, the transport module [comprising] including:
a plurality of wheels attached to a frame;
wherein the frame is adapted to detachably receive at least the first computer storage module and the first battery serving module.
17. (Original) The computer servicing cart of claim 10 further comprising a ventilation system.

June 19, 2006
Case No.: 18534.53 (8125/4)
Serial No.: 10/716,094
Filed: November 18, 2003
Page 7 of 13

18. (Currently Amended) The computer servicing cart of claim 1 further comprising:

a second computer storage module;

a second power supply disposed in the first battery servicing module; and

[a power shredding circuit comprising] wherein the power shredding circuit further includes:

[a first and second relay adapted to connect the first and second computer storage modules, respectively, to the external outlet;]

[a current sensing device adapted to measure the current drawn from the external outlet; and]

a second relay in electrical communication with the first internal power supply, the second relay including means for selectively connecting the first internal power supply to the second computer storage module; and

[a logic circuitry adapted for]:

wherein the logic circuit includes:

means for closing the first and second relays, and activating the second power supply in a predetermined order when the first power supply is activated;

means for opening the relays and deactivating the second power supply in a predetermined order when the current sensing device indicates [a] the current being drawing from the external electrical outlet in excess of [a] the predefined limit;

means for recording a relay or power supply and a current drawn by the relay or power supply that caused the current drawn that is over the predefined limit;

means for monitoring the current drawn from the external outlet such that a deactivated power supply or an opened relay can be activated or closed respectively when the current drawn from the external outlet has fallen enough to allow reactivation or closing without causing current to be drawn that is in excess of the predefined limit; and

means for deactivating the second power supply and opening the first and second relays when the first power supply is deactivated.

June 19, 2006
Case No.: 18534.53 (8125/4)
Serial No.: 10/716,094
Filed: November 18, 2003
Page 8 of 13

19. (Withdrawn) A power shedding circuit for selective disconnection of loads from a power source to prevent overloading, the power shedding circuit comprising:

a current sensing device for monitoring current drawn from an external electrical outlet;

a plurality of logical outputs to indicate a power on or power off state for a plurality of devices powered by the outlet;

logic circuitry adapted for:

setting the logical outputs from power off, to power on, in a predetermined order when the power shedding circuit is activated;

setting the logical outputs from power on, to power off, in a predetermined order when the current sensing device indicates a current being drawn from the outlet that is in excess of a predetermine limit;

recording a logical output, and the current drawn, that cause the current to be drawn from the outlet that is in excess of the predefined limit;

monitoring the current drawn from the external outlet such that a logical output set to power off can be set back to power on when the total current from the outlet has fallen enough to allow powering on without causing the current in excess of the predefined limit to be drawn from the outlet; and

setting the logical outputs to power off when the shedding circuit is deactivated.

20. (Withdrawn) The power shedding circuit of claim 19 wherein:

the current sensing device comprises a Hall effect sensor;

the logic circuitry comprises a microcontroller;

at least one of the logical outputs is adapted to power up an external device by use of a relay connected from the external device to the outlet.